## **POWER UNITS**

# DIT

**SPECIFICATION** 



Isuzu Power Solutions. For those who never stop.











# GLANCE

**Power Output** Max. 29.1 kW / 39.0 hp (rated)

@ 2800 RPM

■ Max. 24.7 kW / 33.2 hp (cont.)

@ 2800 RPM

**Torque Output** ■ Max. 119 Nm @ 1900 RPM

**Displacement** ■1.496 L

**Bore x Stroke** ■ 84 x 90 mm

■ 613 mm (L) O/A Dimensions (engine only) ■ 509 mm (W)

■ 756 mm (H)

**Dry Weight** (engine only) ■157 kg

**Features** 

■ Turbocharged diesel engine

■ Mechanical direct injection fuel system

■ Low noise, low fuel consumption, low maintenance

■ Compact and easy to start

■ Reliable power

■ Water cooled

■ Interim Tier-4 emission compliance

■ Genuine Isuzu engine manufactured in Japan

#### PERFORMANCE ENGINE **Engine Power** 1200 1400 1800 2000 2200 2400 2600 2800 1600 Rated (kW / hp) 13.0 / 17.4 15.9 / 21.3 18.8 / 25.2 22.2 / 29.8 24.7 / 33.1 26.4 / 35.4 28.0 / 37.5 29.1 / 39.0 29.0 / 38.9 Continuous (kW / hp) 11.1 / 14.8 13.5 / 18.1 16.0 / 21.4 18.9 / 25.3 21.0 / 28.2 22.4 / 30.1 23.8 / 31.9 24.7 / 33.1 24.7 / 33.2



# **SPECIFICATIONS**

Туре:	Vertical water-cooled 4-cycle Diesel	
Model (Manufacturer):	3CD1T-BKZP1 (Isuzu)	
Engine Emission:	Interim Tier-4 / Stage-IIIA	
Max. Rated Output:	29.1 kW (39.0 hp) @ 2800 RPM	
Continuous Output:	24.7 kW (33.2 hp) @ 2800 RPM	
Max. Torque	119 Nm @ 1900 RPM	
Displacement:	1.496 L	
Combustion System:	Direct Injection (Turbocharged)	
O/A Dimensions:	613 (L) x 509 (W) x 756 mm (H)	
Dry Weight:	157 kg	
Fuel Consumption:	9.2* L/h @ 100% load	

\*Based on diesel fuel with a specific gravity of 0.835 kg/m3 at 15°C. Actual value may vary.

#### **POWER UNIT CONFIGURATIONS**

#### 1. Starter (STR)

- Medium duty air cleaner system
- · Industrial grade exhaust system
- Engine mounting feet
- Heavy duty full aluminium cooling system (max. 45°C)
- 12V complete electrical system (incl. engine harness and stop solenoid)

#### 2. Economy (ECY)

#### Features include STR plus:

- Skid rail chassis mounting
- Mechanical vernier throttle kit
- IP65 'ECO' engine controller (essential watchdog protection)

#### 3. Premium (PRM) Features include ECY plus:

- · Air cleaner restriction indicator
- Air cleaner rain/inlet hood
- High performance heavy duty cooling system (50°C +)
- Engine oil pressure and temperature senders
- IP65 'PRO' engine controller (advanced watchdog protection + application I/O)
- · Remote oil drain kit

# KEY BENEFITS

#### DESIGN

Australian designed and sourced engine mounts and skid

Australian designed heavy duty bar and plate all aluminium radiator

Premium quality air cleaner

Complete electrical engine harness (includes engine stop solenoid, glow plug assisted start and fuel pump.

### CONTROL PANEL

Murphy 'ECO' economy engine controller (provides essential engine monitoring protection)

ComAp 'PRO' professional engine controller

(advanced engine monitoring protection, plus customer application inputs/outputs, complete event history log, large easy to read display)



Murphy 'ECO' Controller



ComAp 'PRO' Controller

## OPTIONS

Premium pump pressure transducer range

Longer application skid for mounting of auxiliary items

Heat Exchanged cooling package

Flywheel stub shafts

Auxiliary PTO crankshaft pulley

4G remote monitoring and control kit

Low coolant alarm protection kit 160W solar battery charging kit

Extension harnesses

Electronic throttle actuator system

Coolant surge tank kit

Vibration isolation mounts



Transducer option



Heat Exchanger option



Clutch option