POWER UNITS

БНКІХЧ

SPECIFICATION

POWER SOLUTIONS

Isuzu Power Solutions. For those who never stop.











AT A GLANCE

Power Output ■ Max. 212.0 kW / 284.3 hp

rated) @ 2000 RPM ■ Max. 180.2 kW / 241.6 hp

(cont.) @ 2000 RPM

Torque Output ■ Max. 1125 Nm @ 1500 RPM

Displacement ■ 7.8 L

Bore x Stroke ■ 115 x 125 mm

O/A Dimensions ■ 1362 mm (L) (engine only) ■ 865 mm (W)

■ 1074 mm (H)

Dry Weight (engine only)

■ 640 kg

Features

■ Turbocharged intercooled diesel engine

■ Common rail direct injection fuel system

■ Low noise, low fuel consumption, low maintenance

■ Easy to start

■ Reliable power

■ Water cooled

■ Tier-3 emission compliance

■ Genuine Isuzu engine manufactured in Japan

ENGINE PERFORMANCE 1500 **Engine Power** 1000 1100 1200 1300 1400 1600 1700 1800 1900 2000 Rated (kW / hp) 82.0 / 110.0 98.0/131.4 112.0/150.2 140.0/187.7 155.0/207.9 176.7/237.0 189.0/253.4 198.0/265.5 205.0/274.9 209.0/280.3 212.0/284.3 Continuous (kW / hp) 95.2/127.7 119.0/159.6 131.8/176.7 150.2/201.4 160.7/215.4 168.3/225.7 174.3/233.7 177.7/238.2 180.2/241.6



SPECIFICATIONS

Туре:	Vertical water-cooled 4-cycle Diesel		
Model (Manufacturer):	6HK1-XYBW02 (Isuzu)		
Engine Emission:	Tier-3 / Stage-IIIA		
Max. Rated Output:	212.0 kW (284.3 hp) @ 2000 RPM		
Continuous Output:	180.2 kW (241.6 hp) @ 2000 RPM		
Max. Torque	1125 Nm @ 1500 RPM		
Displacement:	7.8 L		
Combustion System:	Direct Injection (Turbocharged, Intercooled)		
O/A Dimensions:	1362 (L) x 865 (W) x 1074 mm (H)		
Dry Weight:	640 kg		
Fuel Consumption:	54.3* L/h @ 100% load		
*Based on diesel fuel with a specifi	c gravity of 0.835 kg/m3 at 15°C. Actual value may vary.		

POWER UNIT CONFIGURATIONS

1. Starter (STR)

- Light duty air cleaner system
- Industrial grade exhaust system
- Engine mounting feet
- Heavy duty full aluminium cooling system (max. 45°C)
- 24V complete electrical system (incl. engine harness and stop solenoid)

2. Premium (PRM) Features include STR plus:

- Heavy duty air cleaner system (dual element)
- Air cleaner restriction indicator
- Residential grade exhaust system
- · Skid rail chassis mounting
- High performance heavy duty cooling system (50°C +)
- IP65 'PR0' engine controller (advanced watchdog protection + application I/O)
- Remote oil drain kit

KEY BENEFITS

DESIGN

Australian designed and sourced engine mounts and skid Australian designed heavy duty bar and plate all aluminium radiator Premium quality air cleaners Complete electrical engine harness (includes engine stop solenoid, glow plug assisted start, fuel feed pump) IP65 stainless steel ECM enclosure with LED indicators

CONTROL PANEL

ComAp 'PRO' professional engine controller (advanced engine monitoring protection, plus customer application inputs/outputs, complete event history log, large easy to read display)



ComAp 'PRO' Controller

OPTIONS

Flywheel stub shafts
Premium pump pressure transducer range
4G remote monitoring and control kit
Low coolant alarm protection kit
160W solar battery charging kit
Extension harnesses
Coolant surge tank kit
12V electrical system
Vibration isolation mounts







Clutch option